

CR65 & CR65 ICHP MicroTurbine Renewable



Robust power system achieves ultra-low emissions and reliable electrical/thermal generation from waste gas.

- Years of renewable experience
- Ultra-low emissions
- Operates on landfill or digester gas
- One moving part – minimal maintenance and downtime
- Patented air bearing – no lubricating oil or coolant
- 5 and 9 year Factory Protection Plans available
- Remote monitoring and diagnostic capabilities
- Integrated utility synchronization and protection
- Small, modular design allows for easy, low-cost installation
- Reliable – tens of millions of run hours and counting
- Dual Mode option available for digester gas operation

C65 MicroTurbine

Electrical Power Output	65kW
Voltage	400–480 VAC
Electrical Service	3-Phase, 4 wire
Frequency	50/60 Hz, grid connect operation
Maximum Output Current	100A, grid connect operation 100A, stand alone operation ⁽²⁾⁽³⁾
Electrical Efficiency LHV	29%

Landfill Gas HHV	13.0–22.3 MJ/m ³ (350–600 BTU/scf)
Digester Gas HHV	20.5–32.6 MJ/m ³ (550–875 BTU/scf)
H ₂ S Content	< 5,000 ppmv
Inlet Pressure	517–552 kPa gauge (75–80 psig)
Fuel Flow HHV	888 MJ/hr (842,000 BTU/hr)
Net Heat Rate LHV	12.4 MJ/KWh (11,800 BTU/kWh)

C65 ICHP MicroTurbine

NOx Emissions @ 15% O ₂ ⁽⁴⁾	< 9 ppmvd (18 mg/m ³)
NOx / Electrical Output ⁽⁴⁾	0.16 g/bhp-hr (0.46 lb/MWhe)
Exhaust Gas Flow	0.49 kg/s (1.08 lbm/s)
Exhaust Gas Temperature	309°C (588°F)

C65 ICHP Heat Recovery⁽⁵⁾

Integrated Heat Recovery Module Type	Stainless Steel Core
Hot Water Heat Recovery	70kW (0.24 MMBTU/hr)

Dimensions & Weight⁽⁶⁾

	CR65	CR65 ICHP
Width x Depth ⁽⁷⁾ x Height ⁽⁸⁾	0.76 x 2.0 x 1.9 m (30 x 77 x 75 in)	0.76 x 2.2 x 2.36 m (30 x 87 x 93 in)
Weight - Grid Connect Model	758 kg (1,671 lb)	1000 kg (2,200 lb)
Weight - Dual Mode Model ⁽²⁾	1121 kg (2,471 lb)	1364 kg (3,000 lb)

Minimum Clearance Requirements⁽⁹⁾


	CR65	CR65 ICHP
Horizontal Clearance		
Left & Right	0.76 m (30 in)	0.76 m (30 in)
Front	0.76 m (30 in)	0.76 m (30 in)
Rear	0.91 m (36 in)	0.76 m (30 in)

Sound Levels

	CR65	CR65 ICHP
Acoustic Emissions at Full Load Power ⁽¹⁰⁾		
Nominal at 10 m (33 ft)	70 dBA	65 dBA

Certifications

- Classified UL 2200 and UL 1741 for raw natural gas and biogas operation (UL file AU5040)
- Complies with IEEE 1547 and meets statewide utility interconnection requirements for California Rule 21 and the New York State Public Service Commission
- Models available with optional equipment for CE Marking



- (1) Nominal full power performance at ISO conditions: 59°F, 14.696 psia, 60% RH
 (2) Only applies to digester gas (and Capstone "Type-B" fuels) only
 (3) With linear load
 (4) For surrogate landfill and digester gases. Please contact Capstone for additional details
 (5) Heat recovery for water inlet temperature of 60°C (140°F) and flow rate of 2.5 l/s (40 GPM)
 (6) Approximate dimensions and weights
 (7) Depth includes 10 inch extension for the heat recovery module rain hood on ICHP versions
 (8) Height dimensions are to the roof line. Exhaust outlet extends at least 7 inches above the roof line
 (9) Clearance requirements may increase due to local code considerations
 (10) The optional acoustic inlet hood kit can reduce acoustic emissions at the front of the MicroTurbine by up to 5 dBA
 Specifications are not warranted and are subject to change without notice.

